

# Index

Page numbers followed by f and t indicate figures and tables, respectively.

## A

- Absorption chillers; *see also* Chillers
  - cost estimates for, 266, 266t
  - double-effect (2E), 371
    - exhaust absorption chiller, 277, 278f
    - Li-Br, 273, 277
  - schematic, 266, 267f
  - single-effect (1E), 264–265, 265f, 371
  - types, 277, 278t
  - water/LiBr, 266
- Absorption cooling systems, 97–100
- Absorption TES
  - performance improvement, 397–399, 398f
  - working pairs, 393–394, 395t
  - working principle, 385, 388–389, 388f
- Active systems, solar water heating systems, 331, 331f
- Active thermal energy storage systems, 240–243
- Actuator problems, 423
- Actuators, 192
- Adaptive fault detection, 435
- Adsorption TES
  - performance improvement, 399–400, 400f
  - for space cooling, 403–404, 405f
  - test facility, 403–404, 405f
  - working pairs, 394, 396–397
    - silica gel and water, 394
    - zeolites and water, 394, 396–397, 396f, 397f
  - working principle, 389–392, 390f, 391f, 392f
- Advanced Automated HVAC
  - Fault Detection and Diagnostics Commercialization project, 448
  - AFUE (annual fuel utilization efficiency), 113–114, 117
- Aggregated thermal demand (ATD) method, extended, 270–271
- Air conditioning energy consumption, 475–496
  - case study sites, 478, 480, 480f, 481f, 482f
  - future work, 495–496
  - methodology for case study, 483–490
    - BEM, 485–488, 487f, 487t, 488f
    - BEP, 484–485
    - SBEM, EnergyPlus™, 488–490, 489f, 490f
    - uWRF, city scale model, 483, 483f
  - overview, 475–478, 477f, 478t, 479t
  - results and discussion, 490–495
    - dark roof AC energy consumption simulation, 490, 492f
    - SBEM sensitivity analysis, 493–495, 495f
    - SBEM vs. uWRF, 493, 494f
    - TMY weather file, 490, 491f
    - total energy demand, 492, 493f
    - uWRF weather outputs data, 490, 491f
  - summer 2010 heat wave event, 481, 482
  - US National and regional studies, 478, 479t
- Air conditioning (A/C) technology, building, 349–358
  - chilled water storage/aquifers, 349–352, 350f, 351f, 352t
  - PCMs, 352, 353–354
    - ceiling board, 357, 357f, 358
  - cumulative energy saving of load levelling strategy, 355t
  - free cooling systems, 355f

- ice TES system, schematic diagram, 353f
- for solar shading, 354, 355, 356f, 357, 357t
- various thermal storage systems, 354t
- Air conditioning (A/C) technology, solid desiccant, 268–269
- Air-cooled condensers, 104–105
- Air handling units (AHU), 124–127
  - diagnostic algorithms for, 437, 440
  - diagram, 453, 454f
  - FDD methods, 438t–439t
  - fresh air ventilation rates, 126–127
- Air humidity, 484
- Air supply temperature control loop, 131
- Alarm functions, 206
- Alarm management, 421–424
  - PMM, 424, 425f
  - process/system fault definition, 422–423, 423f
- Algorithms for recovery times estimation, 219–220
- Allocation, costs and investment, 344–345
- AM10 Natural Ventilation in Non-Domestic Buildings, 154
- Analysis
  - economic and feasibility, CCHP systems, 279–283
  - cost, 282, 283t
  - detailed electricity and natural gas usage, 280, 280t
  - electric and natural gas costs, 281, 283t
  - electric output, 281, 281t
  - heat output, 281, 282t
- Anova Verzekering Co., 352
- APAR & VPACC, 446t
- Applications
  - FDD, challenges in, 450–452
  - strategy/approach related, 451–452
  - industrial and HVAC, fault detection methods, 441–449
  - business models and commercial solutions, 443
  - commercial software, 443, 444t–447t
  - hardware/software requirements, 442–443
  - implementations, review of, 443, 448–449
  - solar ventilation air preheating, 320
  - TES, 348
- Aquifers
  - chilled water storage, 349–352, 350f, 351f, 352t
  - hot water tank, 358–361, 358f, 360f
- Arizona Public Service (APS), 281
- Artificial lighting, annual use of, 214
- Artificial neural networks (ANN), 202; *see also* Intelligent control systems
  - PCA and, 435–436
- Artificial neuro-fuzzy inference system (ANFIS), 435
- ASHRAE 62.1, 150
- ASHRAE (American Society of Heating, Refrigerating, and Air-Conditioning Engineers), 113, 127, 260, 328
- ASHRAE 188: Prevention of Legionellosis Associated with Building Water Systems, 161
- ASHRAE 62.1 standard, 150
- ASHRAE Standard 52, 161
- ASHRAE Standard 55, 149
- ASHRAE Standard 62, 221, 226
- ASHRAE Std. 189.1, 10
- ASME Boiler and Pressure Vessel Code, 115
- ASME ISBES Workshop, 8–10
- AspenTech, 443
- Automated fault detection and diagnosis, in HVAC systems, *see* Fault detection and diagnosis (FDD)
- Autoscaling, defined, 430
- Azeotrope, 96

## B

BACnet, 442  
BACnet device, 209  
Bahnfleth's solution, 35  
Bayesian-Emulator approach, 86–88  
BEM (building energy model), 483, 483f, 485–488, 487f, 487t, 488f  
Benefits, TES, 270–271  
BEopt™ (Building Energy Optimization) software, 5  
BEP (building energy parameterization), 483, 483f, 484–485  
Bishop, 42  
BLAST, 42, 84  
Boiler Efficiency Institute, 117  
Boilers, 110–124  
  control for, 236  
  electric heat pumps, 120–121  
  electric resistance heating, 119  
  low-temperature radiant heating systems, 121–124  
  selection, 115–116  
Bottoming cycle, CCHP systems, 271  
Boundary layer  
  defined, 320  
  temperature, 321  
Building automation systems (BAS), 204  
  implementation, 443  
Building Description Language (BDL), 83  
Building energy model (BEM), 483, 483f, 485–488, 487f, 487t, 488f  
Building Energy Modeling, 4–5  
Building energy parameterization (BEP), 483, 483f, 484–485  
Building integrated PV (BIPV), 299  
Building integration, CCHP (case studies), 271–279  
Building level challenges and solutions, ESI, 337–341  
  overcurrent protection, 337f, 338, 339

  sizing, 337, 338  
  voltage regulation, 338f, 339  
  wear-and-tear on reactive power compensation equipment, 340–341, 340f  
Building load coefficient (BLC), 76, 82  
Building loads, 240  
Building management & control systems (BEMS), 443  
Building management systems (BMS), 204  
Building Optimization System program, 448  
Building systems control strategies, 5–6  
Building thermal mass, precooling of, 236–239  
Buildings  
  CCHP in, *see* Combined cooling, heating and power (CCHP) systems  
  energy storage systems for, *see* Energy storage systems  
  FDD application, challenges in, 450–452  
  strategy/approach related, 451–452  
  sorption TES system for, 385, 388–407  
  working principle, 385, 388–392  
  with TES integration literature summary, 375–379, 376t–378t  
Buoyancy-driven natural ventilation, 143, 153–154  
Business models, industrial and HVAC application, 443

## C

C ratio, defined, 258  
Cadmium telluride, 296–297  
Caissons, concrete, 298  
Calcium chloride, 107  
California Energy Commission, 448  
Carnot cycle method, 120

Carnot Refrigeration Cycle, 94–97  
 Case studies; *see also* District cooling systems (DCS), fault detection system for (case study); Fault detection system for DCS (case study); Passive cooling, case studies  
 air conditioning energy consumption methodology, 483–490  
 sites, 478, 480, 480f, 481f, 482f  
 CCHP sizing options, building integration, operation and system controls, 271–279  
 fault detection system for DCS  
 design and features, 454–455, 455f  
 implementation results, 455–461, 456t, 457f, 457t, 459f, 460f  
 process layout and specifications, 452–453, 453f, 454f  
 fault detection system for district cooling systems, 452–464  
 Cast-iron boilers, 115  
 CCHP, *see* Combined cooling, heating and power (CCHP) systems  
 Ceiling board, PCM, 357, 357f, 358  
 Center for Research and Technology Development (CRTD), 2  
 Central communications controller (CCC), 205  
 Central control unit (CCU), 205  
 Central inverters, 301  
 Challenges  
 building level, ESI, 337–341  
 overcurrent protection, 337f, 338, 339  
 sizing, 337, 338  
 voltage regulation, 338f, 339  
 wear-and-tear on reactive power compensation equipment, 340–341, 340f  
 in FDD application, 450–452  
 strategy/approach related, 451–452  
 substation-level, ESI  
 grid-level, 342–343  
 network protectors in systems, 341–342  
 RE on local substation, 341  
 Chilled water storage/aquifers, sensible TES with, 349–352, 350f, 351f, 352t  
 Chiller water loops and VAV systems, 127–133  
 energy recovery systems, 132–133  
 Chiller-priority control strategy, 240  
 Chillers, 100; *see also* Absorption chillers  
 control for, 235  
 recommendations for chiller system operation in commercial buildings, 105–106  
 set-point temperature, 244, 245  
 Chlorofluorocarbons (CFCs), 96  
 City scale model, uWRF, 483, 483f  
 Classification  
 fault detection methods, 424, 425–436  
 commonly used methods, 427–429, 428f, 429f  
 current trends, 435–436  
 overview, 424, 425  
 PCA, 430–434, 432f, 434f  
 traditional alarm management, prismatic approach, 425–427, 426f  
 sensible/latent TES systems, 348, 349f  
 Climate change and sustainable buildings, 17–18  
 Climate Consultant, 145–146  
 ClockWorks, 444t  
 Closed loop system, 192  
 Coefficient of performance (COP), 98–99  
 GAX with, 265  
 ground-source heat pump, 369  
 Li-Br 2E absorption chiller, 277  
 space cooling/heating, 268  
 standalone solid desiccant systems, 269  
 Collectors, solar water heating  
 efficiency curves, 329, 329f  
 evacuated tube, 326–327, 334–335  
 glazed flat plate, 326, 332t  
 integrated-collector-storage collectors, 330

- parabolic-trough, 327–328
- types, 324–335, 325f
- unglazed, low temperature, 325–326, 330, 332t
- Combined cooling, heating and power (CCHP) systems, 251–284
  - absorption chillers
    - cost estimates for, 266, 266t
    - double-effect (2E), 273, 277, 278f
    - schematic, 266, 267f
    - types, 277, 278t
    - water/LiBr, 266
  - bottoming cycle, 271
  - building integration, case studies, 271–279
  - combined cycle, 271
  - conventional systems vs., 252–253, 253f
  - cooling technology, matching, 261
  - datacenter
    - electric and cooling demand for, 272–273, 273f
    - electric LDC of, 274, 274f
    - two-dimensional LDC for, 275–276, 275f, 276f
  - economic and feasibility analysis, 279–283
    - cost analysis, 282, 283t
    - detailed electricity and natural gas usage, 280, 280t
    - electric and natural gas costs, 281, 283t
    - electric output, 281, 281t
    - heat output, 281, 282t
  - future, 284
  - goal, 271
  - heat recovery, 254, 261, 262–264, 263t
  - installation, 281, 282f
  - operation, case studies, 271–279
  - overview, 252–253, 253f
  - prime movers, 260–261, 260f, 262t
  - sizing options, case studies, 271–279
  - system controls, case studies, 271–279
  - technology, state-of-the-art review, 254–260
    - basic elements, 254
    - commercial application, 256
    - general diagram, 254–255, 254f
    - key system parameters and characteristics, 259, 259t
    - large-scale CCHP systems, 258
    - micro-CCHP systems, 256–257
    - overall efficiency, 255
    - performance, evaluation, 256
    - schematic diagram, 255, 255f
    - technical potential, 256, 257f
    - tri-generation, 259
  - TES requirements/benefits, 270–271
  - thermally activated, 264–269
    - absorption and vapor-compression chillers, 265–266, 266t, 267f
    - category, 264
    - ejector heat pump cycle, 269, 270f
    - single-effect (1E) absorption cycle, 264–265, 265f
    - solid desiccant A/C technology, 268–269
    - standalone liquid desiccant A/C, 269
  - topping cycle, 271
- Combined production of heating and power (CHP), TES and, 370–375
- CCHP system
  - diagram of, 371, 372f
  - hot water heat TES systems, 373–374, 374f
  - performance, 372, 373t
  - general layout, 370, 371f
- Commercial building lighting and window designs, 16–17
- Commercial solutions, industrial and HVAC application, 443
- Communication protocol, 209–210; *see also* Supervisory controllers
- Compressor integration, absorption TES performance, 398, 398f
- Concrete caissons and footers, 298
- Conduction transfer functions (CTFs), 34, 41–43

- Constant-air volume (CAV), 225
  - Contaminants in buildings, 126
  - Control modes, 198–201
  - Control strategies
    - applications
      - about, 210–211
      - electrical systems, 211–218, 212t, 215t, 218t
      - HVAC equipment operation, 221–236, 223t
      - HVAC systems with thermal storage, 236–246
      - optimal start of HVAC systems, 218–221
    - control modes, 198–201
    - control system components, 190–198, 191t, 195t
    - intelligent control systems
      - about, 201
      - artificial neural networks, 202
      - expert controls, 202
      - fuzzy control, 202
    - overview, 189–190
    - supervisory controllers
      - communication protocol, 209–210
      - components of EMCS, 204–206
      - design considerations of EMCS, 207–209
      - functions of ECMS, 206–207
      - types of, 202–203
  - Controller bias, 199
  - Conventional systems, CCHP systems
    - vs., 252–253, 253f
  - Cool tower ventilation, 152
  - Cooling by desiccant equipment, 106–109
  - Cooling coil fouling, 457, 458, 461, 459f, 460f
  - Cooling demands
    - building heating and, 272
    - for data center, 272–273, 273f
  - Cooling load avoidance, 313–319, 317f
  - Cooling towers, 101–103
  - Cooling vapor compression systems, 94–97
  - Cooling/heating central plant
    - optimization, 234–236
  - Cost(s)
    - CCHP systems
      - analysis, 282, 283t
      - electric and natural gas, 281, 283t
    - of daylighting system, 311
    - energy, TES and, 352
    - estimates, for absorption and vapor-compression chillers, 266, 266t
    - installation of PV system, 301–302
    - Interconnection Requirement Study, 336
    - solar ventilation air preheating, 319, 320, 323t
    - solar water heating systems, 332t, 333, 334–335
    - utilities' electrical generation systems, 344–345
  - Crop drying, solar ventilation air preheating, 319
  - Crown Casino and Entertainment Complex, 448–449
  - CSIRO Energy Transformed Flagship, 449
  - Current-voltage relation, of PV cell, 295–296, 295f
  - Cycling stability, defined, 380
- D**
- DABO™, 445t, 449
  - Data centers, 17
    - in commercial sector, 256
    - cooling LDC of, 274–275, 275f
    - electric and cooling demand, 272–273, 273f
    - electric LDC of, 274, 274f
    - two-dimensional LDC for, 275–276, 275f, 276f
  - Data transmission medium (DTM), 206
  - Data-driven approach
    - defined, 427
    - review, 429, 429f
  - Daylighting, 305–313, 312f

- Daylighting control system, 213–218, 213f, 214f, 215t, 218t; *see also* Electrical systems
  - Daylighting simulation tool, 216
  - DCS, *see* District cooling systems (DCS)
  - Dehumidification, 106–107, 125
    - solid desiccant, 268
  - Demand controlled ventilation (DCV), 225–228, 228t
  - Demand side management (DSM), 343
  - Dense urban environments, air conditioning energy consumption in, *see* Air conditioning energy consumption
  - Department of Energy (DOE), 256
  - Desiccant equipment, cooling by, 106–109
  - Designs
    - direct gain, 315–316
    - FDD, 454–455, 455f
  - Desorber, defined, 265
  - Detection, fault, *see* Fault detection and diagnosis (FDD)
  - Diagnosis, fault, *see* Fault detection and diagnosis (FDD)
  - Dichlorodi-fluoromethane, 97
  - Dimensionality reduction technique, PCA as, 433
  - Direct digital control (DDC) systems, 202, 203
  - Direct gain
    - defined, 315
    - designs, 315–316, 317f
  - Discharging method
    - double stage, 398–399, 398f
    - three phase cycle, 398f, 399
  - Discussion, air conditioning energy consumption, 490–495, 491f, 492f, 493f, 494f, 495f
  - District cooling systems (DCS), fault detection system for (case study), 452–464
    - design and features, 454–455, 455f
    - implementation results, 455–461
    - cooling coil fouling, 457, 458, 461, 459f, 460f
    - historical data set clusters
      - classification, 457, 457f
      - monitored variables, 455, 456f
      - recommendations, 461, 464
      - reduced chilled water flow, 457, 461, 462f, 463f
      - statistics thresholds, 457, 457t
    - process layout and specifications, 452–453, 453f, 454f
  - Disturbance parameter change, 422
  - DOE-2, 76, 83, 84–85, 87, 88
  - Double skin facade, 168–173; *see also* Passive cooling
    - design considerations, 170–173
    - performance, 169–170
    - principle, 168–169
  - Double stage discharging method, 398–399, 398f
  - Double-effect (2E) absorption chillers, 371; *see also* Chillers
    - exhaust absorption chiller, 277, 278f
    - Li-Br, 273, 277
  - Downflow furnace, 111–112
  - “Drain down” systems, 331
  - Duty cycling, 210
- E**
- Earth cooling, 143
  - Economic analysis, CCHP systems, 279–283; *see also* Costs
    - cost analysis, 282, 283t
    - detailed electricity and natural gas usage, 280, 280t
    - electric and natural gas costs, 281, 283t
    - electric output, 281, 281t
    - heat output, 281, 282t
  - Economizer systems, 222
  - Ecotect, 145–146
  - Efficiency curves, for solar water heating collectors, 329, 329f
  - Ejector heat pumps, 269, 270f
  - Electric devices, 202

- Electric grid, synchronization of
  - generation equipment on, 342–343
- Electric service, to building with RE
  - overcurrent protection, 337f, 338, 339
  - sizing, 337, 338
  - voltage regulation, 338f, 339
- Electrical generation systems, utilities, 343–345
- Electrical power (maximum), defined, 241–242
- Electrical systems; *see also* Control strategies
  - daylighting control system, 213–218, 213f, 214f, 215t, 218t
  - motor duty cycling controls, 211–213
- Electronic devices, 202
- Electronic thermal anemometer, 222
- Electronicto-pneumatic (E/P) transducers, 203
- EMCS, *see* Energy management and control systems (EMCS)
- Emerging Technologies (ET), 2
- Energy analysis methods, detailed, 70–76
  - heat balance method, 70–73
  - thermal network method, 73–74
  - weighting factors, 74–76
- Energy analysis methods, simplified, 60–70
  - transient thermal network analysis, 67–70
  - variable base degree days method, 60–66
- Energy cost savings, 237–238, 239f
- Energy Information Administration (EIA), 475
- Energy management and control systems (EMCS)
  - about, 189
  - communication protocol, 209–210
  - components of, 204–206
  - cost benefits of, 208
  - design considerations of, 207–209
  - functions of, 206–207
  - size categories, 204
- Energy Management System (EMS), 204
- EnergyPlus, 42, 71–72, 76, 84–85, 87, 233, 243
- EnergyPlus™, SBEM and, 319, 483, 488–490
  - energy sources interaction, 489, 489f
  - model, 489, 490f
  - parametric studies for, 495, 495f
  - SBEM vs. uWRF for Midtown, 493, 494f
  - total energy demand, 492, 493f
- Energy savings from daylighting controls, 213
- Energy storage density (ESD)
  - comparison of, 392, 393f
  - of sensible TES, 385
- Energy storage systems, for buildings, 347–408
  - overview, 347–348
  - sorption TES system for buildings, 385, 388–407
    - performance improvement, 397–407; *see also* Performance improvement
    - working pairs, 392–397; *see also* Working pairs
  - working principle, 385, 388–392
- TES systems, sensibility and latency, 348–385
  - air conditioning, 349–358
  - ceiling board, PCM, 357, 357f, 358
  - ceilings, PCM, 366, 367
  - chilled water storage/aquifers, 349–352, 350f, 351f, 352t
  - CHP and, 370–375, 371f, 372f, 373t, 374f
  - classification, 348, 349f
  - floor heating, PCM, 366, 367f
  - for heating, 358–367
  - heat pumps and, 367–370, 368f, 369f
  - hot water tank/aquifers, 358–361, 358f, 360f



integration literature summary,  
     building with, 375–379,  
     376t–378t  
 latent TES with PCMs, 352, 353–  
     354, 364–365; *see also* Phase  
     change materials (PCMs)  
 materials, 379–383; *see also*  
     Materials, for sensible/latent  
     TES  
 mathematical modeling of  
     storage system, 383, 384–385,  
     386t–387t  
 PCMs, 352–355, 357–358,  
     364–367; *see also* Phase change  
     materials (PCMs)  
 rock and brick reservoir, 361–364,  
     362f, 363f  
 solar shading, PCM for, 354, 355,  
     356f, 357, 357t  
 wallboards, PCM, 365, 366f  
 Energy system integration (ESI),  
     335–345  
     challenges, 336–337  
     challenges and solutions, building  
         level, 337–341  
         overcurrent protection, 337f, 338,  
         339  
         sizing, 337, 338  
         voltage regulation, 338f, 339  
         wear-and-tear on reactive power  
         compensation equipment,  
         340–341, 340f  
     challenges and solutions, grid-level,  
         342–343  
         synchronization of generation  
         equipment, 342–343  
         voltage stability, 342  
     challenges and solutions, substation-  
         level, 341–342  
         network protectors in systems,  
         341–342  
         RE on local substation, 341  
     net metering policies, 335–336  
     utilities, electrical generation  
         systems, 343–345

    allocating costs and investment,  
         344–345  
     ramp-rates and spinning reserve,  
         343–344  
 EQUEST, 83  
 Error transfer function, 197  
 ESI, *see* Energy system integration  
     (ESI)  
 Ethernet local area networks, 209  
 Evacuated tube collectors, 326–327,  
     334–335  
 Evaporative cooling, direct/indirect,  
     158–162; *see also* Passive cooling  
     design considerations, 160–162  
     performance, 159–160  
     principle, 158–159  
 Evaporative cooling systems, 143  
 Expert controls, 202; *see also*  
     Intelligent control systems  
 Exponentially Weighted Moving  
     Average (EWMA) control charts,  
     440, 441

## F

Facility loads, 190  
 Fanger comfort model, 232, 233, 234  
 Fatty acid, as PCM, 353  
 Fault detection and diagnosis (FDD),  
     automated, 421–464  
     alarm management, 421–424  
     PMM, 424, 425f  
     process/system fault definition,  
         422–423, 423f  
     application, challenges in, 450–452  
     strategy/approach related, 451–452  
     classification, 424, 425–436  
     current trends, 435–436  
     most commonly used methods,  
         427–429, 428f, 429f  
     overview, 424, 425  
     PCA, 430–434, 432f, 434f  
     traditional alarm management,  
         prismatic approach, 425–427, 426f  
     for DCS, case study  
         design and features, 454–455, 455f

- implementation results, 455–461, 456t, 457f, 457t, 459f, 460f
  - process layout and specifications, 452–453, 453f, 454f
  - for district cooling systems, case study, 452–464
  - industrial and HVAC applications, 441–449
    - business models and commercial solutions, 443
    - commercial software, 443, 444t–447t
    - hardware/software requirements, 442–443
    - implementations, review of, 443, 448–449
  - recent advances, 436–441, 438t–439t
  - design and features, 454–455, 455f
  - implementation results, 455–461
    - cooling coil fouling, 457, 458, 461, 459f, 460f
    - historical data set clusters
      - classification, 457, 457f
      - monitored variables, 455, 456t
      - recommendations, 461, 464
      - reduced chilled water flow, 457, 461, 462f, 463f
      - statistics thresholds, 457, 457t
    - process layout and specifications, 452–453, 453f, 454f
  - Fault detection system for district cooling systems (case study), 452–464
  - FDD, *see* Fault detection and diagnosis (FDD)
  - FDD CX, 447t
  - Feasibility analysis, CCHP systems, 279–283
    - cost analysis, 282, 283t
    - detailed electricity and natural gas usage, 280, 280t
    - electric and natural gas costs, 281, 283t
    - electric output, 281, 281t
    - heat output, 281, 282t
  - Features, FDD, 454–455, 455f
  - Feedback control system, 192
  - Feed-forward networks, 244
  - Field interface devices (FID), 205, 206
  - Fins, defined, 308
  - Fire marshals, 298
  - Fire-tube boilers, 115
  - First Solar, 297
  - Flat-plate collectors, glazed, 326, 332t
  - Floor heating, PCM, 366, 367f
  - Footers, concrete, 298
  - Fouling, cooling coil, 457, 458, 461, 459f, 460f
  - Fourier’s law of heat conduction, 28
  - Fuel cells, chemical reaction in, 254–255
  - Fuel oil, 112
  - Furnaces, 110–124
    - electric heat pumps, 120–121
    - electric resistance heating, 119
    - low-temperature radiant heating systems, 121–124
  - Fusion heat, of PCMs, 379, 380f
  - Fuzzy control, 202; *see also* Intelligent control systems
- G**
- Gas-to-liquid heat exchangers, 264
  - Gaussian Process (GP) emulator, 87–88
  - Gauss-Jordan Matrix Solver, 41
  - Generator–Absorber heat eXchange (GAX), 265
  - Glazed flat plate collectors, 326, 332t
  - Grid-connected PV system, 300–301, 300f, 305, 305f
  - Grid-level challenges and solutions, 342–343
    - synchronization of generation equipment, 342–343
    - voltage stability, 342
  - Ground-coupled heat transfer, 229f
- H**
- Hardware requirement, industrial and HVAC application, 442–443
  - Harry Thomason’s technique, 361, 362f

- Heat exchanger materials, 134
  - Heat flux modulation techniques, 229
  - Heat generation and transfer
    - equipment, 109–124
    - furnaces and boilers, 110–124
    - introduction, 109–110
  - Heat pumps, TES and, 367–370, 368f, 369f
  - Heat rates, 115
  - Heat recovery, CCHP systems, 254, 261, 262–264, 263t
  - Heat recovery steam generator (HRSG), 258
  - Heat recovery unit (HRU), 255
  - Heat rejection equipment, 101–105
  - Heat transfer concepts, 24–30
    - transient heat transfer from building envelope, 26–30
  - Heat transfer enhancement methods, 383, 384f
  - Heat wave event (summer 2010), 481, 482
  - Heating Degree Days (HDD), 316
  - Heating energy
    - savings, 234
    - use, 231
  - Heating, TES for, 358–367
    - hot water tank/aquifers, 358–361, 358f, 360f
    - PCMs
      - ceilings, 366, 367
      - floor heating, 366, 367f
      - latent TES with, 364–365, 364f, 365f
      - wallboards, 365, 366f
    - rock and brick reservoir, 361–364, 362f, 363f
  - Heating, ventilation and air conditioning (HVAC) systems,
    - automated FDD in, *see* Fault detection and diagnosis (FDD)
  - Helmholtz equation, 35–36
  - Hierarchical kernel learning method, 440
  - High efficiency system integration, 127–133
    - chiller water loops and VAV systems, 127–133
  - High temperature conditions (HTC), 297
  - Hittle, 42
  - Horizontal furnaces, 112
  - Hot water heat TES systems, 373–374, 374f
  - Hot water tank/aquifers, sensible TES with, 358–361, 358f, 360f
  - Hotelling  $T^2$  statistics, 431–432, 432f, 433, 434, 454
  - Houghton Hall Office Building in Luton, UK, 179–180
  - Humidification, 162
  - HVAC equipment operation
    - cooling/heating central plant optimization, 234–236
    - demand controlled ventilation (DCV), 225–228, 228t
    - outdoor air intake controls, 221–225, 223t–224t
    - radiant slab heating systems, 228–234, 234t
  - HVAC mechanical systems, 133–135
    - heat exchanger materials, 134
    - supervisory control systems, 133–134
    - surface enhancing heat transfer, 134–135
  - HVAC system
    - control systems used in, 202
    - optimal start of, 218–221
    - sensors used for, 191t
    - with thermal storage
      - neural network controls of, 243–246
      - passive/active thermal energy storage systems, 240–243
      - precooling of building thermal mass, 236–239
  - Hybrid ventilation, 153–154
  - Hydraulic systems, 203
- I**
- IBM TRIRIGA Energy Optimization, 446t
  - Ice storage system, 242

- Identification, fault, 424, 425f
  - IES-VE, 313
  - Implementations, industrial and HVAC, 443, 448–449
  - Indoor air quality (IAQ), 207, 221, 225
  - Industrial and HVAC applications, fault detection methods, 441–449
    - business models and commercial solutions, 443
    - commercial software, 443, 444t–447t
    - hardware/software requirements, 442–443
    - implementations, review of, 443, 448–449
  - Industrial heat pumps, 121
  - Institute of Electrical and Electronics Engineers (IEEE), Standard 1547, 340–341, 345
  - Integral gain constant, 200
    - derivative control, 200
  - Integrated building automation system (IBAS), 189, 204
  - Integrated-collector-storage collectors, 330
  - Integrated/Sustainable Building Equipment and Systems (ISBES) Initiative, 2
  - Integration
    - literature summary, TES, 375–379, 376t–378t
    - solar energy systems, *see* Solar energy systems
  - Intelligent control systems; *see also* Control strategies
    - about, 201
    - artificial neural networks, 202
    - expert controls, 202
    - fuzzy control, 202
  - Interconnection Requirement Study, 336
  - International Electrotechnical Commission (IEC) standard, 297
  - International Energy Agency (IEA), 347
  - Inverters, dual mode, 301
  - Investment, utilities' electrical generation systems, 344–345
  - I-v curve, of PV cell, 295–296, 295f
- J**
- Journal of Solar Energy Engineering, 2
- K**
- Kathabar, 107–108
  - K-means clustering algorithm, 457, 457f
- L**
- LabView, 442
  - Laplace transform, 193–194
  - Latency, TES, 348–385
    - air conditioning, building, 349–358
      - chilled water storage/aquifers, 349–352, 350f, 351f, 352t
      - PCM ceiling board, 357, 357f, 358
      - PCM for solar shading, 354, 355, 356f, 357, 357t
      - PCMs, 352, 353–354, 353f, 354t, 355f, 355t
    - CHP and, 370–375
      - CCHP system, diagram of, 371, 372f
      - general layout, 370, 371f
      - hot water heat TES systems, 373–374, 374f
      - performance of CCHP plant, 372, 373t
    - classification, 348, 349f
    - for heating, 358–367
      - hot water tank/aquifers, 358–361, 358f, 360f
      - PCM ceilings, 366, 367
      - PCM floor heating, 366, 367f
      - with PCMs, 364–365, 364f, 365f
      - PCM wallboards, 365, 366f
      - rock and brick reservoir, 361–364, 362f, 363f

- heat pumps and, 367–370, 368f, 369f
  - materials, 379–383
    - heat transfer enhancement methods, 383, 384f
    - main features, 382, 382t
    - PCM for TES systems, comparison, 383, 383t
    - PCMs, classification of, 379, 379f
    - PCMs, melting temperature and fusion heat, 379, 380f
    - sensible storage concepts, 380–381, 381t
  - mathematical modeling of storage system, 383, 384–385, 386t–387t
  - TES integration literature summary, building with, 375–379, 376t–378t
  - Lawrence Berkeley National Laboratory (LBNL), 83
  - Lighting energy use savings, 216
  - Lightshelves, defined, 309
  - Limitations, for FDD, 450–451
  - Liquefied propane gas (LPG), 112
  - Liquid desiccant air conditioners (LDACs), 269
  - Lithium chloride, 107
  - Load anticipation, 190
  - Load duration curve (LDC) for data centers
    - cooling, 274–275, 275f
    - electric, 274, 274f
    - two-dimensional, 275–276, 275f, 276f
  - sizing and evaluating building electric power, 273f, 274, 274f
  - Load tracking, 190
  - Local substation, RE on, 341
  - Losses, thermal, 328
  - Low irradiance conditions (LIC), 297
  - Low temperature conditions (LTC), 297
- M**
- Materials
    - for sensible/latent TES, PCMs, 379–383
    - classification of, 379, 379f
    - comparison, 383, 383t
    - heat transfer enhancement methods, 383, 384f
    - main features, 382, 382t
    - melting temperature and fusion heat, 379, 380f
    - sensible storage concepts, 380–381, 381t
    - in solar water heating systems, 329, 330
  - Mathematical modeling, of storage system, 383, 384–385, 386t–387t
  - Mean air temperature (MAT), 229, 232
  - Mean radiant temperature (MRT), 229
  - Measurement and verification (M&V) of energy savings, 78
  - Mechanical cooling equipment, 100
  - Mechanical draft towers, 103
  - Melting temperature, of PCMs, 379, 380f
  - Methodology for case study, air conditioning energy consumption, 483–490
    - BEM, 485–488, 487f, 487t, 488f
    - BEP, 484–485
    - SBEM, EnergyPlus™, 488–490, 489f, 490f
    - uWRF, city scale model, 483, 483f
  - Micro-inverters, 301
  - Mitalas, 42
  - Modeling
    - building air conditioning energy consumption, *see* Air conditioning energy consumption
    - mathematical, of storage system, 383, 384–385, 386t–387t
  - Modules, defined, 294
  - Montreal Protocol, 96
  - Motor duty cycling controls, 211–213; *see also* Electrical systems
  - Multi-level switching controls, 309
  - Multiple boilers, control for, 235
  - Multiple chillers control, 235; *see also* Chillers

Multiplexer (MUX), 206  
 Multi-scale PCA (MPCA), 435

**N**

National Electrical Manufacturers Association (NEMA), 211  
 National Weather Service (NWS), 481  
 Natural gas, 258  
 Natural ventilation, 147–154; *see also*  
   Passive cooling  
   design considerations, 150–154  
   performance, 148–150  
   principle, 147–148

Net metering  
 defined, 335  
 policies, 336  
 PV for, 336

Neural network controls, 243–246  
 Neurons, 202  
 Night cooling, 143  
 Night cooling with thermal mass,  
   154–157; *see also* Passive cooling  
   design considerations, 155–157  
   performance, 154–155  
   principle, 154

NN-based optimal controller, 244,  
 245, 245f

Nominal operating cell temperature  
 (NOCT), 297, 304

NREL Chemical Storage Facility,  
 323–324, 324f

NYCMetNet, 482, 482f

**O**

Offline model training, 454  
 One-zone controls of carbon-di-oxide,  
 228  
 Online FDD, 454  
 Open loop systems, 192  
 OpenStudio, 313  
 Operating differential, 198  
 Operation, CCHP (case studies),  
 271–279  
 Operative temperature (OT), 229

Optimal daylighting controller, 216  
 Outdoor air flow, 227  
 Outdoor air intake controls, 221–225,  
 223t–224t

Overcurrent protection, on electrical  
 service, 337f, 338, 339

Overhangs  
 defined, 308  
 window, 315

**P**

PACRAT, 447t  
 Palais des congrès de Montréal, 449  
 Panoptix Continuous Diagnostic  
 Advisor, 444t

Parabolic-trough collectors, 327–328

Paraffin  
 organic heat storage materials, 382  
 wax, as PCM, 353

Parallel duty cycling, 212

Parameter change  
 disturbance, 422  
 process, 422

Passive cooling, 142–143  
 case studies, 179–184  
 direct/indirect evaporative cooling,  
 158–162  
 double skin facade, 168–173  
 natural ventilation, 147–154  
 night cooling with thermal mass,  
 154–157  
 overview, 143–145  
 phase change material, 173–179  
 prescreening feasibility, 145–147  
 Sunspace, 165–168  
 Trombe Wall, 162–165

Passive design strategies, 6, 8

Passive solar heating, 143–144,  
 313–319  
 computer tools for, 319  
 direct gain, 315–316, 317f  
 equations for, 318  
 sunspace, 316, 317f  
 Trombe Wall, 316, 317f  
 window overhang, 315

Passive systems, solar water heating systems, 330  
 Passive thermal energy storage systems, 240–243  
 Pattern matching method, 440  
 PCMs, *see* Phase change materials (PCMs)  
 Penetration limits, defined, 336  
 Performance, of CCHP plant, 372, 373t  
 Performance improvement, sorption TES system, 397–407  
   absorption, 397–399, 398f  
   adsorption, 399–400, 400f  
   prototypes and systems, 400–407  
   adsorption TES test facility, 403–404, 405f  
   closed H<sub>2</sub>O/CaCl<sub>2</sub>, 400, 403, 403f  
   H<sub>2</sub>O/silica gel, 403, 404f  
   H<sub>2</sub>O/13X zeolite, 405, 406f  
   recent achievements, 400, 401t–402t  
   solar sorption pilot plant, 406, 406f  
 Phase change materials (PCMs), 173–179; *see also* Passive cooling  
   ceiling board, 357, 357f, 358  
   ceilings, 366, 367  
   classification of, 379, 379f  
   design considerations, 177–179  
   floor heating, 366, 367f  
   latent heat of, 315  
   latent TES with, 352, 353–354, 364–365  
   cross-sectional view of heat storage tank, 364f  
   cumulative energy saving, 355t  
   free cooling systems, 355f  
   paraffin wax, 365f  
   schematic diagram, 353f  
   thermal storage systems, comparison, 354t  
   melting temperature and fusion heat, 379, 380f  
   performance, 174–177  
   principle, 173–174  
   for solar shading, 354, 355, 356f, 357, 357t  
   Stefan problem for, 383, 384  
   TES units, 374  
   wallboards, 365, 366f  
 Photo-sensor system, 216, 217f  
 Photovoltaics (PVs), 292–305  
   BIPV, 299  
   cadmium telluride, 296–297  
   cells, equivalent circuit diagram, 294, 295f  
   effect, 292  
   grid-connected, 300–301, 300f, 305, 305f  
   IEC standard, 297  
   initial, operation and maintenance costs, 303t  
   i-v curve, 295–296, 295f  
   roof racks, 298  
   short-circuit operating current, 294  
   solar insolation, map of, 292, 293f  
   solar resource, map of, 292–294, 293f  
   wear-and-tear on reactive power compensation equipment, 340–341, 340f  
 Pierce two-node model, 233, 234  
 Piles, 298  
 Pitot-tube array station, 222  
 Plenum, defined, 322  
 Plenum pressure control, 225  
 Pneumatic devices, 202  
 Policies, net metering, 336  
 Polycarbonate, 365  
 Polymer electrolyte membrane fuel cells (PEFC/PEMFC), 258  
 Polynomial transfer function, 48  
 Porosity, defined, 320  
 Power combustion furnaces, 112  
 Power generation unit (PGU), 254, 255  
 Power-to-heat ratio, defined, 370  
 Pre-cooling control strategy, 237–238, 237f  
 Pre-cooling energy savings, 239t  
 Precooling of building thermal mass, 236–239

Predicted mean vote (PMV), 232  
 Predicted mean vote modified by  
   effective temperature (PMVET), 233  
 Predictive control strategy, 243  
 Preheating, ventilation air, *see* Solar  
   ventilation air preheating  
 Primary land use tax lot output  
   (PLUTO), 486, 487f  
 Prime movers, for CCHP systems,  
   254, 260–261, 260f, 262t  
 Principal component analysis (PCA)  
   ANN and, 435  
   fault detection method, 430–434,  
     432f, 434f  
   FDD design and feature, 454–455,  
     455f  
   MPCA, 435  
   operational flow diagram, 434, 434f  
 Prismatic approach, traditional alarm  
   management, 425–427, 426f  
 Prismatic regions, defined, 426  
 Process monitoring method (PMM),  
   424, 425f  
 Process parameter change, 422  
 Proportional control system, 199–200  
 Proportional gain constant, 199  
 Proportional-plus-integral control (PI  
   control), 200  
 Proportional-plus-integral-plus  
   derivative (PID) control, 200, 201f,  
   226, 228  
 Propylene glycol, 331, 332  
 Protectors, in network systems,  
   341–342  
 Protocol implementation conformance  
   statement (PICS), 210  
 Prototypes, sorption TES system,  
   400–407  
   adsorption TES test facility, 403–  
     404, 405f  
   closed H<sub>2</sub>O/CaCl<sub>2</sub>, 400, 403, 403f  
   H<sub>2</sub>O/silica gel, 403, 404f  
   H<sub>2</sub>O/13X zeolite, 405, 406f  
   recent achievements, 400, 401t–402t  
   solar sorption pilot plant, 406, 406f

PRRMSE indicators, 88  
 Public Interest Energy Research  
   (PIER), 448  
 Public Utilities Commission (PUC),  
   336  
 PVs, *see* Photovoltaics (PVs)

## Q

Qualitative model-based methods,  
   FDD, 428–429, 428f  
 Quantitative model-based methods,  
   FDD, 427–429, 429f

## R

Racks, roof, 298  
 Radial Basis Function (RBF) neural  
   network, 441  
 Radiant gains, 328  
 Radiant slab heating systems, 228–  
   234, 234t  
 Radiant systems, 121–124  
 Ramp-rates, 343–344  
 RC thermal network technique,  
   67–69  
 Reactive power compensation  
   equipment, 340–341, 340f  
 Recent trends, in FDD methods,  
   436–441, 438t–439t  
 Reciprocating engines, 258, 261  
 Recovery time, 219  
 Reduced chilled water flow, 457, 461,  
   462f, 463f  
 Regeneration process, 98, 268  
 Regression analysis, 219  
 Renewable energy (RE) systems  
   advantages, 291  
   electric service to building with  
     overcurrent protection, 337f, 338, 339  
   sizing, 337, 338  
   voltage regulation, 338f, 339  
   on local substation, 341  
 Requirements  
   hardware/software, industrial and  
     HVAC application, 442–443  
   TES, 270–271



- Resources, solar, 292–294, 293f
- Results, air conditioning energy
  - consumption, 490–495, 491f, 492f, 493f, 494f, 495f
- RETScreen, 279
- Reynolds averaged form, defined, 484
- RMI Headquarters Building: Amory Lovins Uber Solar Home in Colorado, US, 180, 182–184
- Rock and brick reservoir, 361–364, 362f, 363f
- Roof racks, 298
- Rotor angle stability, defined, 342
  
- S**
- Salt hydrates, 382
- Saturation enthalpy, 108–109
- SBEM, *see* Single building energy model (SBEM)
- SCIwatch®, 445t
- Screws, 298
- Secondary systems, 124–127
  - fresh air ventilation rates, 126–127
- Sensibility, TES, 348–385
  - air conditioning, building, 349–358
    - chilled water storage/aquifers, 349–352, 350f, 351f, 352t
    - PCM ceiling board, 357, 357f, 358
    - PCM for solar shading, 354, 355, 356f, 357, 357t
    - PCMs, 352, 353–354, 353f, 354t, 355f, 355t
  - CHP and, 370–375
    - CCHP system, diagram of, 371, 372f
    - general layout, 370, 371f
    - hot water heat TES systems, 373–374, 374f
    - performance of CCHP plant, 372, 373t
    - TES integration literature summary, building with, 375–379, 376t–378t
  - classification, 348, 349f
  - ESD of, 385
  - for heating, 358–367
    - hot water tank/aquifers, 358–361, 358f, 360f
    - PCM ceilings, 366, 367
    - PCM floor heating, 366, 367f
    - PCM wallboards, 365, 366f
    - rock and brick reservoir, 361–364, 362f, 363f
  - heat pumps and, 367–370, 368f, 369f
  - materials, 379–383
    - heat transfer enhancement methods, 383, 384f
    - main features, 382, 382t
    - PCM for TES systems, comparison, 383, 383t
    - PCMs, classification of, 379, 379f
    - PCMs, melting temperature and fusion heat, 379, 380f
    - sensible storage concepts, 380–381, 381t
    - mathematical modeling of storage system, 383, 384–385, 386t–387t
- Sensors, 191
- Shaft energy, 254
- Shockley, William, 294, 295
- Short-circuit operating current, of PV module, 294
- Sick Building Syndrome (SBS), 140, 149–150
- Silica gel, water and, 394, 403, 404f
- Single building energy model (SBEM)
  - AC compressor work in, 488
  - energy consumption for, 493
  - Energy Plus, 489
  - energy sources interaction, 489f
  - ensemble of, 475–476
  - sensitivity analysis, 493, 495f
  - solutions to uWRF, 487
  - thermal zones, 489
  - by TMY weather file, 475, 490, 494
  - using US Department of Energy, 483
  - uWRF *vs.*, 493, 494f
- Single chiller control, 235
- Single-effect (1E) absorption chillers, 264–265, 265f, 371

- Sizing
  - of electrical service to building, 337, 338
  - options, CCHP (case studies), 271–279
- SkySpark, 444t, 448
- Software requirement, industrial and HVAC application, 442–443
- Sol-air temperature, 71–72
- Solar energy systems, integration of, 291–345
  - cooling load avoidance, 313–319, 317f
  - daylighting, 305–313, 312f
  - ESI, 335–345
    - allocating costs and investment, 344–345
    - building level challenges and solutions, 337–341; *see also* Building level challenges and solutions
    - challenges, 336–337
    - grid-level challenges and solutions, 342–343
    - net metering policies, 335–336
    - ramp-rates and spinning reserve, 343–344
    - substation-level challenges and solutions, 341–342
    - utilities, electrical generation systems, 343–345
  - overview, 291–292
  - passive solar heating, 313–319
    - computer tools for, 319
    - direct gain, 315–316, 317f
    - equations for, 318
    - sunspace, 316, 317f
    - Trombe Wall, 316, 317f
    - window overhang, 315
  - photovoltaics, 292–305
    - BIPV, 299
    - cadmium telluride, 296–297
    - cells, equivalent circuit diagram, 294, 295f
    - effect, 292
      - grid-connected, 300–301, 300f, 305, 305f
      - IEC standard, 297
      - initial, operation and maintenance costs, 303t
      - i-v curve, 295–296, 295f
      - roof racks, 298
      - short-circuit operating current, 294
      - solar insolation, map of, 292, 293f
      - solar resource, map of, 292–294, 293f
    - ventilation air preheating, 319–324
      - applications, 320
      - components, 321, 322f
      - costs, 319, 320, 323t
      - maintenance requirements, 319
      - NREL Chemical Storage Facility, 323–324, 324f
      - potential energy delivery, map of, 319, 320f
      - transpired solar collector and bypass damper, 323, 324f
  - water heating systems, 324–335
    - active systems, 331, 331f
    - collectors, types, 324–335, 325f
    - costs, 332t, 333, 334–335
    - efficiency curves, 329, 329f
    - evacuated tubes, 326–327, 334–335, 334f
    - glazed flat plate collectors, 326, 332t
    - integrated-collector-storage collectors, 330
    - materials and components, 329, 330
    - parabolic-trough collectors, 327–328
    - passive systems, 330
    - SRCC, 328–329
    - unglazed collector, low temperature, 325–326, 330, 332t
- Solar heat gain coefficient (SHGC), 308, 314
- Solar insolation, map of, 292, 293f
- Solar Rating & Certification Corporation (SRCC), 328–329

Solar resource, map of, 292–294, 293f

Solar shading, PCMs for, 354, 355, 356f, 357, 357t

Solar ventilation air preheating, 319–324

- applications, 320
- components, 321, 322f
- cost, 319, 320
- initial cost, operation and maintenance cost, 323t
- maintenance requirements, 319

NREL Chemical Storage Facility, 323–324, 324f

potential energy delivery, map of, 319, 320f

transpired solar collector and bypass damper, 323, 324f

Solar water heating (SWH) systems, PCM-charged, 364–365, 364f, 365f

Solid desiccant A/C technology, 268–269

Solid oxide fuel cells (SOFC), 258

Solutions

- building level challenges and, ESI, 337–341
- overcurrent protection, 337f, 338, 339
- sizing, 337, 338
- voltage regulation, 338f, 339
- wear-and-tear on reactive power compensation equipment, 340–341, 340f

substation-level challenges, ESI

- grid-level, 342–343
- network protectors in systems, 341–342
- RE on local substation, 341

Sorption TES system for buildings, 385, 388–407

performance improvement, 397–407

- absorption, 397–399, 398f
- adsorption, 399–400, 400f
- prototypes and systems, 400–407, 401t–402t, 403f, 404f, 405f, 406f
- working pairs, 392–397
- absorption, 393–394, 395t
- adsorption, 394, 396–397, 396f, 397f
- ESD, comparison of, 392, 393f
- working principle, 385, 388–392
- absorption, 385, 388–389, 388f
- adsorption, 389–392, 390f, 391f, 392f

Southwest Gas Corporation (SWG), 281

Spherical geometry, models for, 385, 386t–387t

Spinning reserve, 343–344

Squared prediction error, defined, 434

Stack ventilation, 151, 152

Staggered duty cycling, 212

Standalone solid desiccant A/C technology, 268–269

Standard, IEC, 297

Standard test conditions (STC), 297

Steel boilers, 115

Stefan-Boltzmann equation, 123

Stefan problem, for PCMs, 383, 384

Stephenson, 42

Storage-priority control strategy, 240

Strategy/approach related challenges, FDD application, 451–452

String inverters, 301

Substation-level challenges and solutions, ESI

- network protectors in systems, 341–342
- RE on local substation, 341

Summer 2010 heat wave event, 481, 482

Sun Shot program, 134

SunPower, 297

Sunspace, 165–168; *see also* Passive cooling

- design considerations, 167–168
- passive solar heating strategy, 316, 317f
- performance, 166–167
- principle, 165–166
- temperature of, 316

- Supervisory control and data acquisition (SCADA), 442
  - Supervisory control systems, 133–134
  - Supervisory controllers; *see also*
    - Control strategies
    - communication protocol, 209–210
    - components of EMCS, 204–206
    - design considerations of EMCS, 207–209
    - functions of ECMS, 206–207
  - Support vector data description (SVDD) algorithm, 440
  - Support vector regression (SVR) models, 440
  - Surface enhancing heat transfer, 134–135
  - Switching controls, 309
  - System(s)
    - controls, CCHP (case studies), 271–279
    - sorption TES, 400–407
      - adsorption TES test facility, 403–404, 405f
      - closed H<sub>2</sub>O/CaCl<sub>2</sub>, 400, 403, 403f
      - H<sub>2</sub>O/silica gel, 403, 404f
      - H<sub>2</sub>O/13X zeolite, 405, 406f
      - recent achievements, 400, 401t–402t
      - solar sorption pilot plant, 406, 406f
- T**
- Temperature-modulation control, 229
  - Temperatures
    - solar water heating system, 331–332
    - unglazed collector, 330, 332t
  - Tennessee Eastman process, 435
  - TES, *see* Thermal energy storage (TES)
  - Thermal comfort, 232, 233
  - Thermal energy storage (TES)
    - applications, 348
    - defined, 348
    - requirements/benefits, 270–271
    - sensibility and latency, 348–385
      - air conditioning, 349–358
      - ceiling board, PCM, 357, 357f, 358
      - ceilings, PCM, 366, 367
      - chilled water storage/aquifers, 349–352, 350f, 351f, 352t
      - CHP and, 370–375, 371f, 372f, 373t, 374f
      - classification, 348, 349f
      - floor heating, PCM, 366, 367f
      - for heating, 358–367
      - heat pumps and, 367–370, 368f, 369f
      - hot water tank/aquifers, 358–361, 358f, 360f
      - integration literature summary, building with, 375–379, 376t–378t
      - latent TES with PCMs, 352, 353–354, 364–365; *see also* Phase change materials (PCMs)
      - materials, 379–383; *see also* Materials, for sensible/latent TES
      - mathematical modeling of storage system, 383, 384–385, 386t–387t
      - PCMs, 352–355, 357–358, 364–367; *see also* Phase change materials (PCMs)
      - rock and brick reservoir, 361–364, 362f, 363f
      - solar shading, PCM for, 354, 355, 356f, 357, 357t
      - wallboards, PCM, 365, 366f
      - sorption TES system for buildings, 385, 388–407
        - performance improvement, 397–407
        - working pairs, 392–397
        - working principle, 385, 388–392
    - Thermal energy storage (TES) systems
      - active and passive systems, 240–243
      - neural network controls of, 243–246
    - Thermal losses, 328
    - Thermally activated cooling systems, 264–269
      - absorption and vapor-compression chillers, 265–266, 266t, 267f
      - category, 264
      - ejector heat pump cycle, 269, 270f
      - single-effect (1E) absorption cycle, 264–265, 265f

- solid desiccant A/C technology, 268–269
  - standalone liquid desiccant A/C, 269
  - Thermal mass, 154, 157
  - Thermal sensation vote (TSV), 233
  - Thermocline, 358
  - Three phase cycle discharging method, 398f, 399
  - Topping cycle, CCHP systems, 271
  - Traditional alarm management, prismatic approach, 425–427, 426f
  - Trane Intelligent Services, 445t
  - Transfer function, 194, 197f
  - Transient building envelope energy analysis, 30–59
    - conduction transfer function (CTF) methods, 41–44
    - finite difference methods, 31–34
    - frequency-domain regression (FDR) method, 45–53
    - interzone temperature profile estimation (ITPE) techniques, 34–41
    - response factors, 53–59
  - Transient System Simulation Program (TRNSYS) modeling, 364
  - Triethylene glycol, 107
  - Trigeneration, defined, 252
  - TRNSYS, 42, 76, 85
  - Trombe Wall, 162–165, 316, 317f; *see also* Passive cooling
    - design considerations, 164–165
    - performance, 163–164
    - principle, 162–163
  - Turbulent kinetic energy, 485
  - Two-position control system, 198–199
  - Two-zone controls of carbon-di-oxide, 228
  - Typical Meteorological Year (TMY), 319, 483, 490, 491f, 492
- U**
- Unglazed collector, low temperature, 325–326, 330, 332t
  - Upflow furnace, 111
  - Urban heat island (UHI) effect, 476–477, 477f, 478t
  - Urbanized weather forecasting model (uWRF)
    - building parameters for locations, 486–487, 487t
    - city scale model, 483, 483f
    - PLUTO and, 486
    - SBEM *vs.*, 493, 494f
    - TMY and, 492
    - weather outputs, 490, 491f
  - Utilities, electrical generation systems, 343–345
    - allocating costs and investment, 344–345
    - ramp-rates and spinning reserve, 343–344
  - UWRF, *see* Urbanized weather forecasting model (uWRF)
- V**
- Vapor-compression chillers, 266, 266t
  - Variable air volume (VAV), 221, 225
  - Variable air volume (VAV) systems and chiller water loops, 127–133
  - energy recovery systems, 132–133
  - Variable air volume (VAV) terminal boxes, 453
  - Ventilation, 125
  - Ventilation air, preheating, *see* Solar ventilation air preheating
  - Visible light transmittance (VLT), 308
  - VisualDOE, 83
  - Voltage regulation, on electric service to building with RE, 338f, 339
  - Voltage stability, of electric grid, 342
- W**
- Wallboards, PCM, 365, 366f
  - Water heating systems, solar, 324–335
    - active systems, 331, 331f
    - collectors, types, 324–335, 325f
    - evacuated tube, 326–327
    - glazed flat plate collectors, 326, 332t

- integrated-collector-storage collectors, 330
  - parabolic-trough collectors, 327–328
  - unglazed collector, low temperature, 325–326, 330, 332t
  - costs, 332t, 333, 334–335
  - efficiency curves, 329, 329f
  - evacuated tube, 334–335, 334f
  - materials and components, 329, 330
  - passive systems, 330
  - SRCC, 328–329
  - Water tank, hot water, 358–361, 358f, 360f
  - Water/ammonia ( $\text{NH}_3/\text{H}_2\text{O}$ ), 98
  - Water/LiBr absorption chillers, 266
  - Water/lithium-bromide ( $\text{H}_2\text{O}/\text{LiBr}$ ), 98
  - Water-tube boilers, 115
  - Wear-and-tear on reactive power compensation equipment, 340–341, 340f
  - Web-bulb depression efficiency (WBDE), 159–160
  - Whole-building energy models, 76–89
    - forward modeling methods, 81–86
    - inverse modeling methods, 77–81
    - meta-modeling approach, 86–89
  - Wind-driven natural ventilation, 143, 150–151
  - Working pairs, sorption TES system, 392–397
    - absorption, 393–394, 395t
    - adsorption, 394, 396–397, 396f, 397f
    - silica gel and water, 394
    - zeolites and water, 394, 396–397, 396f, 397f
  - ESD, comparison of, 392, 393f
  - Working principle, of sorption TES system, 385, 388–392
    - absorption, 385, 388–389, 388f
    - adsorption, 389–392, 390f, 391f, 392f
  - World urban database and access portal tools (WUDAPT), 486
  - Wright, Frank Lloyd, 307
- Z**
- Zeolites, water and, 394, 396–397, 396f, 397f, 405, 406f
  - Zero-input response, 43
  - Zion National Park Visitor Center, 152